



**SPECIFICATIONS**

Voltage rating: 200V AC, DC  
 Current rating: 0.5A, AC, DC (AWG#30)  
 Withstanding Voltage: 500V AC/minute  
 Insulation resistance: 100MΩ min  
 Temperature range: -40°C - +80°C  
 Contact resistance: 20mΩ

**TERMINAL**

Part NO: SCT1004T/1005T/1007T  
 Thickness: 0.15mm  
 Wire Range: AWG#30-#32 (OD0.6mm)  
 Material: Phos. Bronze  
 Hardness: H  
 Reel Q'ty: 20,000PCS

OPERATION		DRAW		SCALE	
~ 10	±0.15	Judy Huang	2006/05/02	UNIT	mm
20 ~ 30	±0.30	DESIGN		SIZE	A4
30 ~	±0.50	CHECK	2006/05/02	SHEET	1/1
Angle	± 2'	APPROVE	2006/05/02	PROJ.	
DIM	TOL				
MODIFICATION DESCRIPTION		DRAWING NO.		PART NO.	
0	05/12/27	NEW	SCT1004/1005/1007T	SCT1004T/1005T/1007T	
REV	DATE			TITLE: TERMINAL	
1				DRAWING NO. SCT1004/1005/1007	

**SCONDAR** 森康达电子有限公司  
 SCONDAR ELECTRONIC LIMITED